### §421.283

### BPT LIMITATIONS FOR THE SECONDARY TANTALUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	pounds)	ds per million of tantalum oduced from
Copper	38.380	20.200
Lead	8.484	4.040
Nickel	38.780	25.650
Zinc	29.490	12.320
Tantalum	9.090	
Total suspended solids	828.200	393.900
pH	(1)	(¹)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

### (c) Tantalum sludge leach and rinse.

## BPT LIMITATIONS FOR THE SECONDARY TANTALUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of equivalent pure tantalum powder produced	
Copper	390.100	205.300
Lead	86.230	41.060
Nickel	394.200	260.700
Zinc	299.700	125.200
Tantalum	92.390	
Total suspended solids	8,417.000	4,003.000
<u>pH</u>	( <sup>1</sup> )	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(d) Tantalum powder acid wash and rinse.

## BPT LIMITATIONS FOR THE SECONDARY TANTALUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pound pounds) powder pro	of tantalum
Copper	0.665	0.350
	1	
Lead	0.147	0.070
Nickel	0.672	0.445
Zinc	0.511	0.214
Tantalum	0.158	
Total suspended solids	14.350	6.825
pH	(¹)	( <sup>1</sup> )

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(e) Leaching wet air pollution control.

## BPT LIMITATIONS FOR THE SECONDARY TANTALUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million of equivalent alum powder
Copper	9.272 2.050	4.880 0.976
Nickel	9.370	6.198
Zinc	7.125	2.977
Tantalum	2.196	
Total suspended solids	200.100	95.160
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

#### § 421.283 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

(a) Tantalum alloy leach and rinse.

# BAT LIMITATIONS FOR THE SECONDARY TANTALUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of tantalu powder produced	
Copper Lead Nickel Zinc Tantalum	295.200 64.570 126.800 235.200 103.800	140.700 29.980 85.320 96.850

### (b) Capacitor leach and rinse.

# BAT LIMITATIONS FOR THE SECONDARY TANTALUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million of tantalum oduced from
Coppereadlickel	25.860 5.656 11.110	12.320 2.626 7.474

### **Environmental Protection Agency**

### BAT LIMITATIONS FOR THE SECONDARY TANTALUM SUBCATEGORY—Continued

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
Zinc	20.600	8.484
Tantalum	9.090	

#### (c) Tantalum sludge leach and rinse.

# BAT LIMITATIONS FOR THE SECONDARY TANTALUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of equivalent pure tantalum powder produced	
Copper	262.800	125.200
Lead	57.480	26.690
Nickel	112.900	75.960
Zinc	209.400	86.230
Tantalum	92.390	

(d) Tantalum powder acid wash and rinse.

# BAT LIMITATIONS FOR THE SECONDARY TANTALUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of tantalun powder produced	
Copper	0.448 0.098 0.193 0.357 0.158	0.214 0.046 0.130 0.147

(e) Leaching wet air pollution control.

## BAT LIMITATIONS FOR THE SECONDARY TANTALUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of equivalen pure tantalum powde produced	
Copper	6.246	2.977
Lead	1.366	0.634
Nickel	2.684	1.806
Zinc	4.978	2.050
Tantalum	2.196	

### § 421.284 Standards of performance for new sources.

Any new source subject to this subpart shall achieve the following new source performance standards:

(a) Tantalum alloy leach and rinse.

## NSPS FOR THE SECONDARY TANTALUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of tantalum powder produced	
Copper Lead	295.200 64.570 126.800 235.200 103.800 3,459.000 (¹)	140.700 29.980 85.320 96.850 

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(b) Capacitor leach and rinse.

# NSPS FOR THE SECONDARY TANTALUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millic pounds) of tantalu powder produced fro leaching	
Copper	25.860	12.320
Lead	5.656	2.626
Nickel	11.110	7.474
Zinc	20.600	8.484
Tantalum	9.090	
Total suspended solids	303.000	242.400
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(c) Tantalum sludge leach and rinse.

## NSPS FOR THE SECONDARY TANTALUM SUBCATEGORY

CODOMIZACIA		
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of equivalent pure tantalum powder produced	
Copper	262.800 57.480 112.900 209.400	125.200 26.690 75.960 86.230
Tantalum Total suspended solidspH	92.390 3,080.000 (¹)	2,464.000 (¹)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.5 to 10.0 at all times.